

Wall-mounted Dual-ports

-  Ambient Lighting
-  Convenient Payment Credit Card, No Hassle
-  Easy Install/Maintain Access
-  Easy-to-select Features & Accessories
-  Seamless Installation Rear Cable Entry Option
-  Dual-ports Chargers Reduces time by up to 50%



Easy Options



3-Pieces
Minimalist design, easy assembly

6+ Functions
Easy options, fast Delivery

Up to **45%** Saving
TAA/BABA compliant supply solutions,
avoid high tariffs.

DATASHEET

Model Number	CNAC-32A*2-RGWB-BK01	CNAC-40A*2-RGWB-BK01
Product Type	AC Charging Station	
Input Voltage	208/240V AC, Three-phase	
Input Frequency	50/60 Hz	
Output Voltage	208/240V AC	
Output Current	32A Max x2	40A Max x2
Maximum Power Output	7.7kW x2	9.6kw x2
Input Wire	Hardwired	
Charging Connector Type	2xSAE J1772(Default), NACS Tesla(Optional)	
Cable Length	2x18FT/5.5m Standard (2x25FT/7.5m Optional)	
Charging Modes	Mode3	
Charging Protocols	OCPP 1.6J	
Dimensions (H x W x D)	500*360*176mm(19.7*14.2*6.9inch)	
Weight	31.3lbs(14.2kg)	34.8lbs(15.8kg)
Enclosure Rating	NEMA Type3, IK08	
Operating Temperature	-30°C to 50°C(-22°F to 122°F)	
Operating Humidity	<95% Non-condensing	
Altitude	Up to 2000m	
Protection Function	Undercurrent Protection, Overcurrent Protection, Undervoltage Protection, Overvoltage Protection, Short Circuit Protection, Residual Current Device, Over Temperature Protection, Surge Protection, Ground Fault Protection, Control Pilot Fault Protection, Leakage Protection	
Communication Interface	7Inch Screen, WIFI&Bluetooth/4G	
Control Method	RFID/NFC, POS, OCPP Platform	
Mounting Type	Wall-mounted, Pedestal-mounted	
Compliance Standards	ETL, FCC, Energy Star, CTEP compliance, ISO15118 compliance	
Standards	NEC625,UL817, UL991,UL2231,UL2251,UL2594, OCPP1.6J Compliance	
Warranty Period	2 years	

DATASHEET

Model Number	CNAC-48A*2-RGWB-BK01	CNAC-80A*2-RGWB-BK01
Product Type	AC Charging Station	
Input Voltage	208/240V AC, Three-phase	
Input Frequency	50/60 Hz	
Output Voltage	208/240V AC	
Output Current	48A Max x2	80A Max x2
Maximum Power Output	11.5kW x2	19.2kW x2
Input Wire	Hardwired	
Charging Connector Type	2xSAE J1772(Default), NACS Tesla(Optional)	
Cable Length	2x18FT/5.5m Standard (2x25FT/7.5m Optional)	
Charging Modes	Mode3	
Charging Protocols	OCPP 1.6J	
Dimensions (H x W x D)	500*360*176mm(19.7*14.2*6.9inch)	
Weight	38.4 lbs(17.4kg)	43.7 lbs(19.8kg)
Enclosure Rating	NEMA Type3, IK08	
Operating Temperature	-30°C to 50°C(-22°F to 122°F)	
Operating Humidity	<95% Non-condensing	
Altitude	Up to 2000m	
Protection Function	Undercurrent Protection, Overcurrent Protection, Undervoltage Protection, Overvoltage Protection, Short Circuit Protection, Residual Current Device, Over Temperature Protection, Surge Protection, Ground Fault Protection, Control Pilot Fault Protection, Leakage Protection	
Communication Interface	7Inch Screen, WIFI&Bluetooth/4G	
Control Method	RFID/NFC, POS, OCPP Platform	
Mounting Type	Wall-mounted, Pedestal-mounted	
Compliance Standards	ETL, FCC, Energy Star, CTEP compliance, ISO15118 compliance	
Standards	NEC625,UL817, UL991,UL2231,UL2251,UL2594, OCPP1.6J Compliance	
Warranty Period	2 years	